

Mobil 1 New Life 0W-40

Ultimate Performance Synthetic Engine Oil

Product Description

Mobil 1 is the world's leading synthetic engine oil brand delivering our ultimate performance and protection.

Mobil 1 New life 0W-40 is engineered for the latest engine technology, the ideal product for newer vehicles or older vehicles in good condition, delivering our best all-round performance.

Features and Benefits

Our most advanced formulation, Mobil 1 New Life 0W-40, is designed to minimize wear to help maintain performance like new. It helps protect against sludge and varnish under high stress conditions, keeps contaminants away from critical engine parts, performs in extreme temperatures and helps keeps your engine in top condition. It is our most complete engine oil and is recommended if you drive a more modern vehicle or simply want the best oil for your car.

- Latest OEM and industry approvals
- Factory fill for many of the world's finest vehicles
- High performance basestocks combined with SuperSyn Technology for excellent wear all-round protection
- Excellent low temperature capabilities for rapid engine protection at start-up
- Lower frictional properties for enhanced fuel economy
- Extremely low oil consumption reducing the need for top-up
- Excellent thermal and oxidation stability to help prevent sludge build-up and keep engine clean

Applications

Thanks to extensive cooperative development work with major manufacturers and the application of the latest lubrication technology, Mobil 1 New Life 0W-40 is recommended for virtually all types of modern vehicles where it will provide the ultimate protection and performance even under very demanding driving conditions.

- Latest engine technologies including Turbo-chargers, Direct Injection, Diesels and Hybrids
- High Performance Engines
- Extended Oil Drain
- Nearly all operating conditions, from mild to extreme

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

Mobil 1 New Life 0W-40 meets or exceeds the following industry and builder specifications:

API SM/SL/SJ/CF	X
ACEA A3/B3	X



Mobil 1 New Life 0W-40 meets or exceeds the following industry and builder specifications:

A3/B4	X
-------	---

Mobil 1 New Life 0W-40 Mobil Delvac MX has the following builder approvals:

MB-Approval 229.3; MB-Approval 229.5	X
OPEL Long Life Service Fill GM-LL-A-025; OPEL Diesel Service Fill GM-LL-B-025;	X
BMW LONGLIFE OIL 01	X
VW 502 00; VW 505 00	X
PORSCHE Special Oil List	X

Mobil 1 New Life 0W-40 is recommended for use in applications requiring:

SAAB	X
------	---

Typical Properties

Mobil 1 New Life 0W-40

Viscosity, ASTM D 445	
cSt @ 40° C	78.3
cSt @ 100° C	14
Sulfated Ash, wt%, ASTM D 874	1.2
Phosphorous	0.1
Flash Point, °C, ASTM D 92	230
Density @ 15° C kg/l, ASTM D 4052	0.85
Total Base Number (TBN)	11.3
MRV at -40°C	26242
Viscosity Index	186
HTHS Viscosity, mPa*s @ 150°C, ASTM D 4683	3.7

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet, or will be provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Mobil 1 are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2007 Exxon Mobil Corporation. All rights reserved.